

1. `assertionKill` applies to a single attempt since a time is given in the call, not many attempts.
2. "`vpiAssertionSysKill` considers all attempts in progress as unterminated and disables any further assertions from being started." The terminology "considers ... unterminated" is misleading (particularly with recent additions) and should be changed to "discards ..." like the others.

In 38.5.2 Assertion control Replace:

For the following operators, the second argument shall be a valid assertion handle, and the third argument shall be an attempt start time (as a pointer to a correctly initialized `s_vpi_time` structure):

— Usage example:

```
vpi_control(vpiAssertionKill, assertionHandle, attemptStartTime)
```

— **vpiAssertionKill** discards the given attempts, but leaves the assertion enabled and does not reset any state used by this assertion (e.g., `past()` sampling).

With:

For the following operators, the second argument shall be a valid assertion handle, and the third argument shall be an attempt start time (as a pointer to a correctly initialized `s_vpi_time` structure):

— Usage example:

```
vpi_control(vpiAssertionKill, assertionHandle, attemptStartTime)
```

— **vpiAssertionKill** discards the given attempt **attempts**, but leaves the assertion enabled and does not reset any state used by this assertion (e.g., `past()` sampling).

In 38.5 Replace:

— Usage example: `vpi_control(vpiAssertionSysOff, handle)`

— **vpiAssertionSysOff** disables any further assertions from being started. Assertions already executing are not affected. This control has no effect on pre-existing assertion callbacks.

— **vpiAssertionSysKill** considers all attempts in progress as unterminated and disables any further assertions from being started. This control has no effect on pre-existing assertion callbacks.

With:

— Usage example: `vpi_control(vpiAssertionSysOff, handle)`

— **vpiAssertionSysOff** disables any further assertions from being started. Assertions already executing are not affected. This control has no effect on pre-existing assertion callbacks.

— **vpiAssertionSysKill** **discards** **considers** all attempts in progress **as unterminated** and disables any further assertions from being started. This control has no effect on pre-existing assertion callbacks.